PATENT ABSTRACTS OF JAPAN

02084526 A (11) Publication number:

(43) Date of publication of application: 26.03.1990

(51) Int. CI D06M 10/06

D01F 6/18, D01F 6/38, D01F 9/22, D01F 11/16

// D06M101:40

(21) Application number: 63203889 (22) Date of filing: 18.08.1988 (71) Applicant: ASAHI CHEM IND CO LTD

(72) Inventor: TAKADA JIRO HOSOI KEIZO

(54) PRODUCTION OF HIGH-STRENGTH CARBON FIBER

(57) Abstract:

PURPOSE: To readily obtain carbon fiber of highstrength and high-adhesiveness with low cost and safety by anodizing carbon fiber obtained by baking acrylic fiber having specific lightness difference in an aqueous solution of electrolyte containing nitrate ion.

CONSTITUTION: An acrylic fiber having ≥60 lightness difference by iodine- adsorbing method (prefer-

ably containing 90-97wt.% acrylonitrile) is baked (preferably made to flame-resistant in oxidative atmosphere at 200-400°C and carbonized in inert atmosphere at 1200-1400°C) and resultant carbon fiber is anodized (preferably with 30-400coulomb/g at 30-80°C for 0.1-3 min) in an aqueous solution containing nitrate ion (preferably 1-10 N concentration of nitric acid), then heat-treated (preferably in reducing atmosphere at 300-700°C) to afford a carbon fiber of high-strength.

COPYRIGHT: (C)1990, JPO& Japio